



URSA XPS D N-III-PZ I

Thickness d_N [mm]

80

Thermal conductivity

λ_D [W/(m*K)]

0,035

Thermal resistance

R_D [m²*K/W]

2,25

Reaction to fire

E



URSA XPS D N-III-PZ

DoP-No: 49XPSDN3PZ19101

<http://dop.ursa-insulation.com>

EN 13164:2012+A1:2015

Factory made extruded polystyrene (XPS) foam products

Thermal Insulation for Buildings

T1-CS(10\Y)300-DS(70,90)-DLT(2)5-TR200

URSA Deutschland GmbH, Carl-Friedrich-Benz-Str. 46-48, 04509 Delitzsch

www.ursa.de

/EU/ -T1-CS(10\Y)300-DS(70,90)-DLT(2)5-TR200

/DE/ Anwendung nach DIN 4108-10: DEO-dh,DI,WI,WAP

Bemessungswert der Wärmeleitfähigkeit gemäss DIN 4108-4: 0,036 [W/(m*K)]

/AT/ Produktart: XPS-R nach ÖNORM B6000



011-7D077

2127054



8 435062 213259

Q-8B01-L6 15201012

Length [mm]

1250

Width [mm]

600

Piece(s)

5

Surface [m²]

3,750

Edge



bonus



holsystem