

Declaration of Performance

N° DoP: 2024-003 SA52



Unique identification code of the product-type:	ONDULINE® BFX, ONDULINE® KSK-M
Intended use/es:	Vapor barrier membrane - Sealing layer
Manufacturer:	Onduline 5-7 rue Frédéric Clavel 92150 Suresnes - France
System/s of AVCP:	System 3
Harmonised standard :	EN 13970
Notified body/ies:	1742 - Baustofflabor Nord GmbH

Declared performances:

Essential characteristics	Performance	Tolerance		Harmonised standard
		minimum	maximum	
Reaction to fire (Class)	E	-	-	EN 13970
Watertightness - method B	Pass	-	-	
Thickness (mm)	≥1,5	±0,3		
Tensile strength (longitudinal/transverse direction) (N/50 mm)	≥180 / ≥180	±20%		
Elongation at maximum load (longitudinal/transverse direction) (%)	≥20 / ≥20	-	-	
Flexibility at low temperature (pliability) (°C)	-20	-	-	
Flow resistance at elevated temperature (°C)	≥85	-	-	
Water vapor permeability (Sd) (m)	>1500	-	-	
Dangerous substances ^{1), 2)}	Requirement met (see 5.14 EN 13970)			

NPD* : No Performance Determined
1) Product contains no asbestos and no tar
2) Since there is no European test method, no statement can be made on this.

The performance of the product identified above is in conformity with the set of declared performances in point 7. This declaration of performance is issued, in accordance with Regulation (EU) N° 305/2011, under the sole responsibility of the manufacturer identified above.

Version number : v02

A handwritten signature in black ink, appearing to read 'Nay TAWILE', is written over a horizontal line.

Signed for and on behalf of the manufacturer by:
Nay TAWILE, Managing Director Europe
Suresnes, 12/11/2024